



Aufine PCR Tires

AUFINE GROUP CO.,LIMITED



AUFINE GROUP CO.,LIMITED

Add: No.172 Minjiang Road,Qingdao,China

Tel: 0086-532-8573 8980,8077 2790

Fax: 0086-532-8577 2380

Web: <http://www.aufine.com>

Email: info@aufine.com



SPORT A01

Aufine A01 offers the best in quality, focusing on the 3s-silence, smooth(comfort)and stability.

- **Four Wide Channels**
help evacuate water away from the tread for enhancing wet traction
- **Rib Block & Center Rib**
minimize vibration and enforce handling and braking
- **Large Shoulder Blocks**
reduce noise and improve solid cornering and handling performance at high speeds



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
205/65R15	SPORT A01	94	H	6J	209	647	670	1477	300	44
205/65R15	SPORT A01	94	V	6J	209	647	670	1477	300	44
205/55R16	SPORT A01	91	H	6.5J	214	632	615	1356	300	44
205/55R16	SPORT A01	91	V	6.5J	214	632	615	1356	300	44



RADIAL A02

Aufine A02 provides a quiet and comfort riding and ensures excellent wet and dry road grip performance.

- **Double J-shape Patterns**
depress pattern noise, provide a good orientation and driving stability
- **3 Straight Grooves & Large Lateral Grooves**
aid in water evacuation and minimize hydroplaning
- **Mixed Grooves(Horizontal & Vertical, Deep & Light)**
provide excellent wet and dry road grip, high wear-resisting performance



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
155/70R13	RADIAL A02	75	T	4.5B	157	548	387	853	300	44
165/65R13	RADIAL A02	77	T	5J	170	544	412	908	300	44
165/70R13	RADIAL A02	79	T	5J	170	562	437	963	300	44
175/70R13	RADIAL A02	82	T	5J	177	576	475	1047	300	44
175/65R14	RADIAL A02	82	T	5J	177	584	475	1047	300	44
175/65R14	RADIAL A02	82	H	5J	177	584	475	1047	300	44
175/65R14XL	RADIAL A02	86	T	5J	177	584	530	1168	340	50
175/65R14XL	RADIAL A02	86	H	5J	177	584	530	1168	340	50
185/70R14	RADIAL A02	88	T	5.5J	189	616	560	1235	300	44
185/70R14	RADIAL A02	88	H	5.5J	189	616	560	1235	300	44
195/70R14	RADIAL A02	91	T	6J	201	630	615	1356	300	44
195/70R14	RADIAL A02	91	H	6J	201	630	615	1356	300	44
205/70R14	RADIAL A02	95	T	6J	209	644	690	1521	300	44





SPORT A07

- Asymmetric pattern shape, optimized variable pitch pattern design, provide quiet ride environment.
- Nice driving pleasure comes from strong tread and soft sidewall.
- Perfect handling performance and good cornering performance.
- Silica tread compound for low rolling resistance and good wet grip.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
185/55R14	SPORT A07	80	H/V	6.0J	194	560	450	992	300	44
185/55R15	SPORT A07	82	H/V	6.0J	194	585	475	1047	300	44
195/55R15	SPORT A07	85	H/V	6.0J	201	595	515	1135	300	44
195/55R16	SPORT A07	87	H/V	6.0J	201	620	545	1201	300	44
205/55R16	SPORT A07	91	H/V	6.5J	214	632	615	1356	300	44
215/55R16	SPORT A07	93	H/V	7.0J	226	642	650	1433	300	44
175/60R13	SPORT A07	77	H/V	5.0J	177	540	412	908	300	44
185/60R14	SPORT A07	82	H/V	5.5J	189	578	475	1047	300	44
185/60R15	SPORT A07	84	H/V	5.5J	189	603	500	1102	300	44
195/60R14	SPORT A07	86	H/V	6.0J	201	590	530	1168	300	44
195/60R15	SPORT A07	88	H/V	6.0J	201	615	560	1235	300	44
205/60R15	SPORT A07	91	H/V	6.0J	209	627	615	1356	300	44
205/60R16	SPORT A07	92	H/V	6.0J	209	652	630	1389	300	44
215/60R15	SPORT A07	94	H/V	6.5J	221	639	670	1477	300	44
215/60R16	SPORT A07	95	H/V	6.5J	221	664	690	1521	300	44
225/60R16	SPORT A07	98	H/V	6.5J	228	676	750	1653	300	44
235/60R16	SPORT A07	100	H/V	7.0J	240	688	800	1764	300	44



RADIAL A09

- Four circumferential tread grooves, excellent water drainage, improving wet handling.
- Continuous and wide shoulder block design maintains the stability at cornering and brings precise driving experience.
- Special grooves design to bring the superior quiet effect.
- Special wear-resisting tread compound to provide excellent trip mileage.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
165/65R13	RADIAL A09	77	T	5.0J	170	544	412	908	300	44
165/65R14	RADIAL A09	79	T	5.0J	170	570	437	963	300	44
175/65R14	RADIAL A09	82	T/H	5.0J	177	584	475	1047	300	44
185/65R14	RADIAL A09	86	T/H	5.5J	189	596	530	1168	300	44
185/65R15	RADIAL A09	88	T/H	5.5J	189	621	560	1235	300	44
195/65R14	RADIAL A09	89	T/H	6.0J	201	610	580	1279	300	44
195/65R15	RADIAL A09	91	T/H	6.0J	201	635	615	1356	300	44
205/65R15	RADIAL A09	94	T/H	6.0J	209	647	670	1477	300	44
215/65R15	RADIAL A09	96	T/H	6.5J	221	661	710	1565	300	44
155/70R13	RADIAL A09	75	T	4.5J	157	548	387	853	300	44
165/70R13	RADIAL A09	79	T	5.0J	170	562	437	963	300	44
165/70R14	RADIAL A09	81	T	5.0J	170	588	462	1019	300	44
175/70R13	RADIAL A09	82	T	5.0J	177	576	475	1047	300	44
175/70R14	RADIAL A09	84	T	5.0J	177	602	500	1102	300	44
185/70R13	RADIAL A09	86	T/H	5.5J	189	590	530	1168	300	44
185/70R14	RADIAL A09	88	T/H	5.5J	189	616	560	1235	300	44
195/70R14	RADIAL A09	95XL	T/H	6.0J	201	630	690	1521	340	50
205/70R14	RADIAL A09	98XL	T/H	6.0J	209	644	750	1653	340	50
205/70R15	RADIAL A09	96	T/H	6.0J	209	669	710	1565	300	44
215/70R15	RADIAL A09	98	T/H	6.5J	221	683	750	1653	300	44
225/70R15	RADIAL A09	100	T/H	6.5J	228	697	800	1764	300	44
155/80R13	RADIAL A09	79	T	4.5J	157	578	437	963	300	44



CONQUEROR A11

- Four wide longitudinal grooves ensure excellent effective water evacuation and improve aquaplaning.
- The lateral continuous pattern block, reduces the heat in high speed, ensures the stability at cornering and brings precise driving experience.
- The streamlined pattern shape inside, efficiently water-evacuating and high performance of wet ground.
- Special compound design with low heat generation, and high grip performance provides super dry and wet handling.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
235/70R16	CONQUEROR A11	106	H	7.0J	240	736	950	2094	300	44
245/70R16	CONQUEROR A11	107	H	7.0J	248	750	975	2149	300	44
265/70R16	CONQUEROR A11	112	H	8.0J	272	778	1120	2469	300	44
225/65R17	CONQUEROR A11	102	H	6.5J	228	724	850	1874	300	44
235/65R17	CONQUEROR A11	108XL	H/V	7.0J	240	738	1000	2205	340	50
245/65R17	CONQUEROR A11	107	H	7.0J	248	750	975	2150	300	44
255/65R17	CONQUEROR A11	110	H	7.5J	260	764	1060	2337	300	44
265/65R17	CONQUEROR A11	112	H	8.0J	272	776	1120	2469	300	44
215/60R17	CONQUEROR A11	96	H	6.5J	221	690	710	1565	300	44
235/60R18	CONQUEROR A11	107XL	V/W	7.0J	240	739	975	2149	340	50
255/60R17	CONQUEROR A11	106	H/V	7.5J	260	738	950	2094	300	44
235/55R17	CONQUEROR A11	103XL	V/W	7.5J	245	690	875	1929	340	50
235/55R19	CONQUEROR A11	105XL	V/W	7.5J	245	741	925	2039	340	50
255/55R18	CONQUEROR A11	109XL	V/W	8.0J	265	737	1030	2271	340	50
275/55R17	CONQUEROR A11	109	V	8.5J	284	734	1030	2271	300	44
285/55R18	CONQUEROR A11	113	V	9.0J	297	771	1150	2535	300	44
255/50R20	CONQUEROR A11	109XL	V/W	8.0J	265	764	1030	2271	340	50
265/50R20	CONQUEROR A11	111XL	V/W	8.5J	277	775	1090	2403	340	50
275/50R20	CONQUEROR A11	113XL	V/W	8.5J	284	784	1150	2535	340	50
275/45R20	CONQUEROR A11	110XL	V/W	9.0J	273	756	1060	2337	340	50
295/45R19	CONQUEROR A11	109	W/Y	10.0J	296	739	1030	2271	300	44
275/40R20	CONQUEROR A11	106XL	W/Y	9.5J	278	728	950	2094	340	50
295/40R20	CONQUEROR A11	110XL	W/Y	10.5J	301	744	1060	2237	340	50
255/35R19	CONQUEROR A11	96XL	W	9.0J	260	661	710	1565	340	50



EXPLORER A19 A/T-P

- Four main non-straight grooves and wild lateral block provide strong cross-country performance that deal with all kinds of road easily.
- Three-dimensional pattern design to protect pattern block in severe road.
- Jointless wrapping nylon, two layers of high-tension steel belts, dimensional stability polyester carcass consist the strong tire body, transfer the strong power.
- Particular tread compounds with big pattern blocks and proper sea/land ratio to ensure steady directional stability in all-surface traction and all-weather condition.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
P215/65R16	EXPLORER A19 A/T-P	96	T/H	6.5J	221	686	710	1565	300	44
P225/65R17	EXPLORER A19 A/T-P	100	T/H	6.5J	228	724	800	1764	300	44
P235/65R17	EXPLORER A19 A/T-P	103	T/H	7.0J	240	738	875	1929	300	44
P245/65R17	EXPLORER A19 A/T-P	105	T/H	7.0J	248	750	925	2039	300	44
P265/65R17	EXPLORER A19 A/T-P	110	T	8.0J	272	776	1060	2337	300	44
P215/70R16	EXPLORER A19 A/T-P	99	H	6.5J	221	708	775	1709	300	44
P225/70R16	EXPLORER A19 A/T-P	101	T	6.5J	228	722	825	1819	300	44
P235/70R16	EXPLORER A19 A/T-P	104	T	7.0J	240	736	900	1984	300	44
P245/70R16	EXPLORER A19 A/T-P	106	S	7.0J	248	750	950	2094	300	44
P245/70R17	EXPLORER A19 A/T-P	108	S	7.0J	248	776	1000	2205	300	44
P255/70R16	EXPLORER A19 A/T-P	109/112	S	7.5J	260	764	1030	2271	300	44
P265/70R16	EXPLORER A19 A/T-P	111	T	8.0J	272	778	1090	2403	300	44
P265/70R17	EXPLORER A19 A/T-P	113	T	8.0J	272	804	1150	2535	300	44
P275/70R16	EXPLORER A19 A/T-P	114	S	8.0J	279	792	1180	2601	300	44
P235/75R15	EXPLORER A19 A/T-P	105	S	6.5J	235	733	920	2028	300	44
P245/75R16	EXPLORER A19 A/T-P	109	S	7.0J	248	774	1030	2271	300	44



EXPLORER A19 A/T-LT

- Four main non-straight grooves and wild lateral block provide strong cross-country performance that deal with all kinds of road easily.
- Three-dimensional pattern design to protect pattern block in severe road.
- Jointless wrapping nylon, two layers of high-tension steel belts, dimensional stability polyester carcass consist the strong tire body, transfer the strong power.
- Particular tread compounds with big pattern blocks and proper sea/land ratio to ensure steady directional stability in all-surface traction and all-weather condition.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
31*10.50R15LT	EXPLORER A19 A/T-LT	109	S	8.5J	268	775	1030	3042	350	51
LT215/85R16	EXPLORER A19 A/T-LT	115/112	S	6.0J	216	772	1215/1120	2680/2470	550	80
LT235/85R16	EXPLORER A19 A/T-LT	120/116	S	6.5J	235	806	1380/1260	3040/2780	550	80
LT225/75R16	EXPLORER A19 A/T-LT	115/112	S	6.0J	223	744	1215/1120	2680/2470	550	80
LT235/75R15	EXPLORER A19 A/T-LT	104/101	S	6.5J	235	733	900/825	1985/1820	350	51
LT245/75R16	EXPLORER A19 A/T-LT	120/116	S	7.0J	248	774	1380/1260	3040/2780	550	80
LT265/75R16	EXPLORER A19 A/T-LT	123/120	R	7.5J	267	804	1550/1400	3415/3085	550	80
LT285/75R16	EXPLORER A19 A/T-LT	122/119	R	8.0J	286	834	1500/1360	3305/3000	450	65
LT265/70R17	EXPLORER A19 A/T-LT	121/118	R	8.0J	272	804	1450/1320	3195/2910	550	80



CONQUEROR A08

- Four main grooves provide good driving stability and wet performance.
- Special tread compound, ensure the tire performance stability in all kinds of weather conditions.
- Reasonable pattern area, perfect collocation of every grooves.
- White sidewall rib shows extraordinary appearance.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
P185/75R14	CONQUEROR A08	89	S/T	5.0J	184	634	585	1290	300	44
P195/75R14	CONQUEROR A08	92	S/T	5.0J	196	648	635	1400	300	44
P205/75R14	CONQUEROR A08	95	S/T	5.5J	203	664	695	1532	300	44
P205/75R15	CONQUEROR A08	97	S/T	5.5J	203	689	725	1598	300	44
P215/75R15	CONQUEROR A08	100	S/T	6.0J	216	703	790	1742	300	44
P225/75R15	CONQUEROR A08	102	S/T	6.0J	223	719	850	1874	300	44
P235/75R15	CONQUEROR A08	105	S/T	6.5J	235	733	920	2028	300	44



SUPER SPORT A77

- Super wide road-contacted tread provide high-speed stability, precise drivability, better drive and brake.
- The precise asymmetrical pattern design ensure comfortable and quiet in high speed.
- Dual steel belt with high modulus, reinforces stiffness of tread, high strength bead wire, provides super handling performance.
- Low rolling resistance, heat dissipation tread compound.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
265/30ZR19	SUPER SPORT A77	93XL	W	9.5J	271	643	650	1433	340	50
275/30ZR20	SUPER SPORT A77	97XL	W/Y	9.5J	278	674	730	1609	340	50
225/35R19	SUPER SPORT A77	88XL	W	8.0J	240	641	560	1235	340	50
245/35R19	SUPER SPORT A77	93XL	W	8.5J	248	750	650	1433	340	50
255/35R18	SUPER SPORT A77	94XL	W/Y	9.0J	260	635	670	1477	340	50
225/40R18	SUPER SPORT A77	92XL	W	8.0J	230	637	630	1389	340	50



EXPLORER A17

- Super structure and special profile provide high load capacity and comfortable.
- Perfect location of main grooves and lateral grooves, take the good balance with driving stability and traction performance.
- Continuous tire shoulder pattern block with special sipe suppress unnormal wear effectively.
- High mileage compound.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
185R14C	EXPLORER A17	102/100	R	5.5J	188	650	850/800	1875/1765	450	65
185R15C	EXPLORER A17	103/102	R	5.5J	188	674	875/850	1930/1875	450	65
195R14C	EXPLORER A17	106/104	R	5.5J	198	666	950/900	2095/1985	450	65
195R15C	EXPLORER A17	106/104	R	5.5J	198	693	950/900	2095/1985	450	65
185/75R16C	EXPLORER A17	104/102	R	5.0J	184	684	900/850	1985/1875	475	69
195/75R16C	EXPLORER A17	107/105	R	5.5J	196	698	975/925	2150/2040	475	69
205/75R16C	EXPLORER A17	110/108	R	5.5J	203	714	1060/1000	2335/2205	475	69
215/75R16C	EXPLORER A17	113/111	R	6.0J	216	728	1150/1090	2535/2405	475	69
195/70R15C	EXPLORER A17	104/102	R	6.0J	201	655	900/850	1985/1875	450	65
205/70R15C	EXPLORER A17	106/104	R	6.0J	209	669	950/900	2095/1985	450	65
215/70R15C	EXPLORER A17	109/107	R	6.5J	221	683	1030/975	2270/2150	450	65
225/70R15C	EXPLORER A17	112/110	R	6.5J	228	697	1120/1060	2470/2335	450	65
195/65R16C	EXPLORER A17	100/98	R	6.0J	201	660	800/750	1765/1655	375	55
225/65R16C	EXPLORER A17	112/110	R	6.5J	228	698	1120/1060	2470/2335	475	69
235/65R16C	EXPLORER A17	115/113	R	7.0J	240	712	1215/1150	2680/2535	475	69



WINTER MASTER A99

- Special compound design, can still keep the tread soft and elastic when contact with snow road in low temperature.
- Pattern shape instantly remove water film on the surface of the tire.
- Beautiful leaf form and streamline directional pattern shape, throw the snow which in grooves high efficiency.
- Special profile for winter tire ensures the stability of the driving on snow road.



Size	Pattern	Load Index	Speed	Std.Rim	Section Width mm	Overall Diameter mm	Max.Load		Max.Pressure	
							kgs	lbs	kpa	psi
175/65R14	WINTER MASTER A99	82	T/H	5.0J	177	584	475	1047	300	44
185/65R14	WINTER MASTER A99	86	T/H	5.5J	189	596	530	1168	300	44
195/65R15	WINTER MASTER A99	91	T/H	6.0J	201	635	615	1356	300	44
205/65R15	WINTER MASTER A99	94	T/H	6.0J	209	627	670	1477	300	44
215/65R15	WINTER MASTER A99	96	T/H	6.5J	221	662	710	1565	300	44
185/60R14	WINTER MASTER A99	82	T/H	5.5J	189	578	475	1047	300	44
185/60R15	WINTER MASTER A99	84	T/H	5.5J	189	603	500	1102	300	44
195/60R14	WINTER MASTER A99	86	T/H	6.0J	201	590	530	1168	300	44
195/60R15	WINTER MASTER A99	88	T/H	6.0J	201	615	560	1235	300	44
205/60R15	WINTER MASTER A99	91	T/H	6.0J	209	627	615	1356	300	44
205/60R16	WINTER MASTER A99	92	T/H	6.0J	209	652	630	1389	300	44
215/60R15	WINTER MASTER A99	94	T/H	6.5J	221	639	670	1477	300	44
215/60R16	WINTER MASTER A99	95	T/H	6.5J	221	664	690	1521	300	44
225/60R16	WINTER MASTER A99	98	T/H	6.5J	228	676	750	1653	300	44
235/60R16	WINTER MASTER A99	100	T/H	7.0J	240	688	800	1764	300	44
185/55R14	WINTER MASTER A99	80	T/H	6.0J	194	560	450	992	300	44
185/55R15	WINTER MASTER A99	82	T/H	6.0J	194	585	475	1047	300	44
195/55R15	WINTER MASTER A99	85	T/H	6.0J	201	595	515	1135	300	44
195/55R16	WINTER MASTER A99	87	T/H	6.0J	201	620	545	1201	300	44
205/55R16	WINTER MASTER A99	91	T/H	6.5J	214	632	615	1356	300	44
215/55R16	WINTER MASTER A99	93	T/H	7.0J	226	642	650	1433	300	44

